

EXTREME OUTBACK PRODUCTS

P.O. BOX 3075 VACAVILLE, CALIF. 95696-3075

TEL: 707-447-7711 FAX: 707-447-7722

www.extremeoutback.com

YOUR EXTREMEAIRE FILTER IS PRE-OILED AND READY FOR OPERATION.

FILTER OILING AND CLEANING INSTRUCTIONS

YOUR EXTREMEAIRE COMPRESSOR IS FITTED WITH A WASHABLE AND REUSEABLE FILTER MADE IN THE USA BY UNI FILTER.

UNI FILTER OILING INSTRUCTIONS

UFF-100/104 AEROSOL FILTER OIL: Spray the filter inside and out until the filter has complete coverage with oil. Next work the oil into the foam using your hands. Repeat this step once more, then dab filter with paper towels to remove excess oil. Be sure to clean your rubber mount flange so surface is free of oil on the mounting surface.

UNI FILTER CLEANING INSTRUCTIONS

GREASE CUTTING CLEANER IS NECESSARY FOR PROPER CLEANING!!

UFC-300 UNI FOAM FILTER CLEANER: Spray generous amounts of Uni Cleaner on the inside & outside of the filter. Let it soak approximately 3-4 minutes. Rinse out the filter element in warm water until clean. A second application may be necessary for heavily soiled elements. Next you must let the filter dry completely. Very Important! Re-oil per instructions and re-install.

GREASE CUTTING CLEANER: Products like Simple Green, dish soap, or mild solvents can be used if Uni Cleaner is not available at the time of cleaning. Pour cleaning solution into bucket; dunk the filter in multiple times until clean. Rinse with warm water. Next you must let the filter dry completely. Very Important! Re-oil per instructions and re-install.

**“UNI FILTER” FILTER OIL AND FOAM FILTER CLEANER IS AVAILABLE AT
MOTORCYCLE AND ACCESSORY SHOPS**